

SecurSCAN SY-603

WALK THROUGH METAL DETECTOR

FUNCTIONS AND CHARACTERS:

The **SecurSCAN SY-603** is a new high sensitivity multi zone security metal detector for indoor and outdoor use. The whole structure is consisted of two parts: Left-right detecting gatepost + Mainframe.

There are 6 detecting areas spreading evenly over the left-right detecting gatepost from its top to bottom. Each areas could be set independtely from 0 to 99 sensitivity level.

There are built-in LED indicating lights in both sides of detecting gate. The left-right detecting gatepost is formed up by unified mold, and each of other parts is utilizing waterproof designs.

The structure is in an exquisite design, with light weight and solid stand; therefore, the product can be assembled, disassembled or moved easily.

The product reach the highest standards of waterproof and power leakage protection; it may work properly as normal even the whole device is under the rain.

Unique design of integrated circuits, which is stable in function, strong in anti-interference and free from mistakes in reporting.

More units **SecurSCAN SY-603** could be installed close in a line without problems and interference. In case is possible to change the reference frequency of each units.

Has the function of password protection to prevent any hostile change of parameters by any unauthorized person.

Has the function of Recover systematic parameters by one-key; when you make some mis-operations, you may recover all ex-work settings just by one key.

Has the function to adjust the audio tones, adapting to different usage environments.

Information will be marked down on the front panel e.g. number of persons passed-by, times of alarm, strength of interfering signals, etc.

All the parameters could be change by a remote controller, simple and easy.

The **SecurSCAN SY-603** does no harm to cardiac pacemaker in human body, hearing aid, pregnant woman and CD compact disc, etc

CARATTERISTICHE TECNICHE:

- 6 detection areas
- Passage dimensions: 200 x 72 cm. (H x W)
- External dimensions: 226 x 102 x 34,5 cm. (H x W x D)
- Weight: 70 kg.
- Packaging dimensions: 230 x 50 x 47 cm. (H x W x D)
- Weight packed: 85 kg.
- Working power: AC 110 to 220V, 30W
- Working temperature: -20 to 55°C

