

## XRC 60-40

### X-RAY CONTROL SYSTEM

### PARCELS AND LUGGAGE



Professional multi-energy X-ray system for the control of **packages** and **parcels** and **baggage** of medium-small size in general; allows the identification of **organic and inorganic materials**, including **explosives** and **drugs** and the identification of **weapons**, **trigger devices** and dangerous objects that can create security risks.

The nature of the materials that make up the scanned objects is represented by a predetermined color code:

**organic materials in orange**, **metallic materials in blue**, **inorganic materials in green** and **non-penetrable materials in black**.

The representation of the baggage is **without shadow areas**, and it is possible to automatically signal in real time (with a moving belt) the presence of **dangerous objects** (guns, knives, hacksaws, etc.) with a settable threshold.

#### PHYSICAL PROPERTIES

<b>Tunnel Dimensions:</b>	61 x 44 cm. (WxH)
<b>Overall Size:</b>	208 x 87 x 137 cm. (WxLxH)
<b>Total Weight:</b>	540 kg.
<b>Conveyor Height:</b>	81 cm.
<b>Conveyor Load Capacity:</b>	165 kg. Evenly Distributed
<b>Conveyor Speed:</b>	0,20 mt/sec.
<b>System Power:</b>	230VAC +/- 10% / 60-50 Hz

#### STANDARD FEATURES

Programmable Function Keys  
Parcel Counter  
Date and Time Display  
Virtual Threat Image Projection (TIP)  
Organic/Inorganic Threat Alarm  
Operator Training Program (OTP)  
Self Diagnosis  
Generator Timer  
Automatic Stop Conveyor

#### MAIN FIELDS OF APPLICATION

XRC 60-40 is ideal for checking packages, parcels and small baggage no larger than cm. 61x44, in risk areas including:

- Palaces of Justice
- Penitentiary institutes
- Embassies and border crossings
- Government Offices

# XRC 60-40

## X-RAY CONTROL SYSTEM

## PARCELS AND LUGGAGE

### X-RAY GENERATOR & IMAGE PERFORMANCE

Steel Penetration:	37 mm guaranteed; 39 mm typical
Wire Resolution:	38 AWG guaranteed; 40 AWG typical
Anode Voltage:	170kV, operating at 147kV
Tube Current:	0,7 mA
Beam Direction:	Vertically upward
Cooling:	Oil and forced air cooling

### COMPUTER SPECIFICATIONS

Processor:	Intel Core i5 (or superior)
Monitor:	color 24" LED
Memory:	4GB RAM min.
Video Card:	2GB min.
Hard Drive:	1TB min.
USB Port:	6 ports min.
Operating System:	Linux

### OPERATING ENVIRONMENT

Operating Temperature:	-20° > 50° C
Storage Temperature:	-20° > 50° C
Relative Umidity:	10% > 90% non condensing

### OPTIONAL ACCESSORIES

- External UPS (For system)
- Operator Console (Open-Closed/Adjustable/I-stand)
- 21,5" - 27" Flat Monitor
- Input / Output Rollers
- Test Kit (STP/ASTM)
- Protective Cover
- Search Table
- Tray Return System (Motorized/Gravity)
- Inclined Conveyor
- Ultrasonic Rat Repellent
- Radiation Meter

### HEALTH AND SAFETY

#### HEALTH AND SAFETY

All SecurSCAN X-Ray products meet all applicable international health and safety regulations.

US FDA Federal Standard 21CFR 1020.40

Health and Safety at Work Act 1974-compliant 6: Available

Film Safety: ISO 1600 / 33 DIN

CE Compliance: Certified

FCC & IEC Compatibility: Available

IP 20 Safety: Certified

Maximum level of radiation the exterior panels come in contact with is 0.1 mR/hour

### STANDARD IMAGE PROCESSING FEATURES

- Perfect View (Detail Enhancement) (PV)
- Edge Enhancement (EE)
- Pseudo Color (PS)
- Organic Materials (OM)
- Inorganic Materials (IM)
- Black & White (B/W)
- Inverse Colors (IN)
- High Penetration (HP)
- Variable Edge Enhancement (+E -E)
- Variable Density (+D -D)
- Variable Gamma (+G -G)
- Variable Color Separation (+C -C)
- Zoom (64x)
- Sniper Zoom
- Recall Previous Images
- Manual/Automatic Archive
- Annotated Archive
- Multi Energy Viewer (4 - 6 Color)
- Atomic Number Display (Z Value)

### OPTIONAL FEATURES

- Barcode Reader System
- External Camera Archiving
- Remote Viewing Station
- Recheck Station
- Network Supervisory System (NSS)
- Remote Access Connection
- Smart Card Login

